

Titan XQ 400 AC puls DW

090-005607-00001



WE ARE WELDING

XQ - Process

all in



- **Equipment as delivered:** welding machine, including wheel kit with single cylinder bracket, water cooling and 5 m mains connection lead
- 16 individually configurable programmes for each welding task (JOB)
- Infinitely adjustable arc dynamics (choke effect)
- Adjustable start and end-crater functions
- High-precision, powerful EWM eFeed 4-roll wire feed mechanism for secure feeding of all solid and flux cored wires
- Energy-saving thanks to high efficiency and standby function
- Easy, tool-free change of welding polarity
- Earth fault monitoring (PE protection)
- IP23 spray water protected
- Connection capability for remote control and PM function torch
- Optional network connectivity with ewm Xnet software via LAN or WiFi gateway
- PC interface for PC300 XQ software
- Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355
- * EP 1 563 938, EP 1 944 115, EP 0 743 126, EP 1 726 359, EP 1 640 100

	MIG/MAG	MMA	TIG
Setting range for welding current		5 A - 400 A	
Duty cycle at ambient t.e		40 °C	
80 %		400 A	
100 %		370 A	
Open circuit voltage		82 V	
Mains frequency		50 Hz / 60 Hz	
Mains fuses (slow-blow)		3 x 25 A	
Mains voltage (tolerances)		3 x 400 V (-25 % - +20 %)	
Max. connected load	17.6 kVA	18.6 kVA	13.4 kVA
Recommended generator power	23.8 kVA	25.1 kVA	18.1 kVA
cos φ		0.99	
Efficiency		88 %	
Dimensions machine, LxWxH in mm		1152 x 686 x 976	
Weight, machine		128.5 kg	
EMC class		A	
Insulation class		H	
Protection classification		IP23	
Approvals		S sign , CE sign , EAC sign	
Standards		IEC 60974-1, -2 and -10 CL.A	

25.03.2020